






TECHNICAL FEATURES OF INJECTORS FOR THE APPLICATION:

HEAVY DUTY MULTI POINT&SINGLE POINT INJ. ; BUS, TRUCK, INDUSTRIAL ENGINE, GENERATORS (STATIONARY ENGINE)

	IG6 POTOMAC		IG6 TAURUS II		IG7 DAKOTA HP	IG4 DAKOTA "8L"	
							
FEATURES	<i>Coil Resistance</i> 1 Ohm 12V	<i>Coil Resistance</i> 4,7 Ohm 24V	<i>Coil Resistance</i> 2 Ohm 12V	<i>Coil Resistance</i> 4,7 Ohm 24V	2 Ohm	<i>Coil Resistance</i> 1 Ohm	<i>Coil Resistance</i> 4,7 Ohm
FUEL TYPE ON APPLICATION	CNG		CNG		CNG	CNG	
OPENING TIME (ms)	1,8	2,1	2,4	2,4	1,9	2,7	
MAX FLOW RATE	15,2 KG/H 5 BAR	15,2 KG/H 9 BAR	18 KG/H X CYL. 5 BAR	18 KG/H X CYL. 9 BAR	11KG/H X CYL. 7 BAR	31,1 KG/H X CYL.	
N° OF CYLINDER	1 SINGLE		3, 4, 5 AND 6		2, 3 AND 4	1 SINGLE	
DURABILITY	500 MILLION		500 MILLION		500 MILLION	500 MILLION	
MAX PRESSURE RANGE	5 AND 9	5 AND 9	5 AND 9	5 AND 9	7	8	